

AT-9000/28SP

Managed Layer 2 Gigabit Ethernet ECO-Switch



AT-9000/28SP

28 port Gigabit managed 'Green' switch with 24 100/1000Mbps SFP ports and 4 10/100/100T or SFP combo ports

Overview

One of a series of high performance Gigabit Ethernet switches from Allied Telesis. The AT-9000/28SP provides high performance Layer 2 switching at an affordable fixed configuration platform. The switch brings advanced enterprise features to a more affordable level while supporting the changing needs of the SMB market space to improve the delivery of converged data. Support for jumbo Ethernet frames enables higher throughput of time sensitive data.

Environmentally Friendly ECO-Switch

In keeping with our commitment to environmentally friendly processes and products, the AT-9000/28SP is the first of our new green range of products designed to reduce power consumption, minimize hazardous waste and even reduce office noise pollution. Among many features including the use of high efficiency power supplies, and low power chipsets we have also included an ECO-Switch button on the front panel of the AT-9000/28SP switch. This allows you to conserve additional power by turning off the port and MODE LEDs when they are not required.

Low Power Consumption

Specifically designed for low power consumption, the AT-9000/28SP generates less heat than previous products, which not only results in higher reliability, but also has lower running costs and less impact on the environment.

Ideal for Fiber Distribution or Mixed Copper Fiber

The AT-9000/28SP is ideal for fiber-based installations where traditional copper cabling just won't meet the requirement. The ability to match the fiber SFPs to meet distance, noisy industrial or security requirements is essential in so many network builds. This flexibility combined with an energy efficient Layer 2 platform offers a truly cost-effective alternative to the network designer.

Easy Access Networking

Featuring an industry standard CLI and Allied Telesis' intuitive featured Web interface the advanced features of the AT-9000/28SP are accessible to a wide range of system administrators. The well known CLI and Web interfaces significantly reduce learning time and minimize the cost of deployment.

Secure Management

Only authorized administrators can access the management interface of the AT-9000/28SP. Protocols such as SNMPv3 facilitate this protection of your network with local or remote connections.

Securing the Network Edge

To ensure the protection of your data, it is important to control access to your network. Protocols such as IEEE 802.1x port-based authentication guarantee that only known users are connected to the network. Unknown users who physically connect can be isolated to a pre-determined part of your network offering guests such benefits as Internet access while ensuring the integrity of your private network data.

Key Features

Easy, Well Known Management

- Industry standard CLI
- Simple intuitive, Allied Telesis Web interface
- SNMP

Ideal Product for Classroom or Retail Environment

- 28 active SFP ports
- Lower power consumption
- Near silent operation

Securing the Network at its Most Vulnerable Point

- IEEE 802.1x and port security (limited/dynamic)
- IEEE 802.1x basic port mode
- IEEE 802.1x multiple host mode
- IEEE 802.1x EAP-MD5
- Radius client
- SSH server

All the QoS Needed for an Open Office, Classroom or Retail Store Environment

- Eight priorities queues
- IEEE 802.1p for Layer 2 QoS



AT-9000/28SP | Managed Layer 2 Gigabit Ethernet ECO-Switch

Technical Specifications

Physical Interface

24 100/1000Mbps SFP ports for fiber connectivity
and 4 10/100/1000T or SFP combo ports
RJ-45 console port

System Capacity

128MB RAM
16MB flash memory
8K MAC address
Packet buffer memory 4Mbit

Maximum Bandwidth

Non-blocking for all packet sizes
Throughput 41.6Mpps
Switching capacity 56Gbps
Switch fabric speed 62Gbps
Supports 9216 jumbo packets

Latency

100Mbit > 25.22 usec
1000Mbit > 3.84 usec

Port Configurations

Auto-negotiation, duplex, MDI/MDI-X
IEEE 802.3x flow control / back pressure
Head of Line (HoL)

Storm Control

Broadcast, multicast and unicast (DLF)

Spanning-Tree Support

IEEE 802.1D Spanning-Tree Protocol
IEEE 802.1w Rapid Spanning-Tree
Pass-through BPDU

Link Aggregation

Static port trunk
IEEE 802.3ad LACP link aggregation
Support for 12 groups per device
Trunk can support up to eight members per group

VLANs

Supports up to 4094 VLAN IDs
Support for 255 active VLANs
Port-based
IEEE 802.1Q VLAN tag
GARP
GVRP
GMRP

General Protocols

MAC address aging
Port mirroring
RFC 826 ARP
DHCP
RFC 2131 DHCP client

Administration

Web-based GUI
Industry standard CLI
RFC 854 Telnet
Network Time Protocol
HTTP
TFTP

Quality of Service (QoS)

IEEE 802.1p QoS
Eight priority queues
Strict priority and weighted round robin

Multicast Standards

Layer 2 multicast forwarding and filtering
up to 256 groups
IGMPv1 and IGMPv2

Network Management

RFC 1157 SNMPv1/v2c
RFC 2570 SNMPv3
RFC 1215 SNMP traps
RFC 1213 MIB-II
RFC 1573 Extended interface MIB
RFC 1752 RMON 4 groups:
Stats, History, Alarms, Events

Security

Port security (limited/dynamic)
IEEE 802.1x Basic port base
IEEE 802.1x Multiple host mode
IEEE 802.1x EAP-MD5
RFC 2865 Radius client
SSH server

Power Specifications

AC input electrical ratings 100-240V AC, 1A
Frequency 50/60Hz
Maximum DC current 3.08A
Maximum power consumption 37.42W
Typical power consumption
in eco friendly mode 35.65W¹
Power supply efficiency 85%
Heat dissipation 127.768BTU /hours
Maximum acoustic noise 41.7 dB

Compliance Standards

IEEE 802.3 10T
IEEE 802.3u 100TX with auto-negotiation
IEEE 802.3ab 1000T Gigabit Ethernet
100FX SFP support
1000X SFP support

Environmental Specifications

Operating temp. 0°C to 40°C (32°F to 104°F)
Storage temp. -25°C to 70°C (-13°F to 158°F)
Operating humidity 5% to 90% (non-condensing)
Storage humidity 5% to 95% (non-condensing)

Operating altitude range, up to 3,000 meters
(9,843 feet)

Safety and Electromagnetic

Emissions Certifications

EMI FCC Class A, CISPR 22 Class A,
EN55022 Class A, C-TICK, VCCI
Immunity EN55024, EN61000-3-2 and
EN61000-3-3
Safety UL 60950 (cULus),
EN60950-1 (TUV)
Quality and reliability MTBF — 340,000 hours

RoHS Standards

Compliant with European, China and RoHS standards

Package Description

AT-9000/28SP switch
AC power cord
Management cable (RJ-45 to DB-9)
Rubber feet for desktop installation and
19" rack-mountable hardware kit accessories
Install guide and CLI user's guide available on the CD
and at www.alliedtelesis.com

Physical Specifications

Dimensions 44cm x 25.6cm x 4.4cm
(W x D x H) (17.33" x 10.08" x 1.73")

Weight 4.01 kg (8.85 lbs)

¹ Typical power is measured running 24/28 ports on a sample unit

AT-9000/28SP | Managed Layer 2 Gigabit Ethernet ECO-Switch



AT-9000/28SP switch back panel

Ordering Information

AT-9000/28SP-xx
28 port Gigabit managed switch with 24 100/1000Mbps SFP ports and 4 10/100/1000T or SFP combo ports

Where xx = 10 for US
 20 for no power cord
 30 for UK
 40 for Australian
 50 for European

Accessories

Small Form Pluggables (SFPs)

AT-SPTX
100m, 10/100/1000T, RJ-45, SFP

AT-SPEX
Multi-mode Fiber, 2km, GbE, SFP, 1310nm

AT-SPSX
Multi-mode Fiber, GbE Small Form-factor Pluggable (SFP)
850nm

AT-SPSX/1
Multi-mode Fiber, GbE Small Form-factor Pluggable (SFP)
850nm

AT-SPFX/2
Multi-mode Fiber, 2km, 100FX, SFP, 1310nm

AT-SPFX/15
Multi-mode Fiber, 15km, 100FX, SFP, 1310nm

AT-SPFX/40
Multi-mode Fiber, 40km, 100FX, SFP, 1310nm

AT-SPLX10
Single-mode Fiber, 10km, GbE SFP, 1310nm

AT-SPLX10/1
Single-mode Fiber, 10km, GbE SFP, 1310nm

AT-SPLX40
Single-mode Fiber, 40km, GbE SFP, 1310nm

AT-SPLX40/1550
Single-mode Fiber, 40km, GbE SFP, 1550nm

AT-SPZX80
Single-mode Fiber, 80km, GbE SFP, 1550nm

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000311 Rev.B