

# VERTIV™ GEIST™ VP7557 RACK PDU

Basic, Standard



## OVERVIEW

The Vertiv™ Geist™ Basic Rack PDU delivers reliable power distribution at a competitive price point. The Basic PDU is the entry-level solution in the Vertiv Geist Rack PDU family, providing basic, reliable power distribution in all IT environments.

### Benefits

- Reliable power distribution at a low cost point
- Every unit is tested for reliability and functionality — no batch tests
- Fast, inexpensive customization, including non-standard cord lengths
- Standard three-year warranty, upgraded to five years with early product registration

### Part Number:

VP7557 Basic, Standard

### Power Configuration:

16A, 230/400V WYE, 11.0kW

### Physical Configuration:

66 in / 1683 mm Vertical

**Product Summary:** VP7557 — Basic, Standard, 16A, 230/400V WYE, 3 Phase, Vertical, (36) IEC C13, (6) IEC C19, 3 m power cord with 3P+N+E (IP44), Black Powder Coat.

## Specifications and Options

Quantity Of Inputs	1
Voltage	230/400V WYE
Current	16A
VA per Input (Load Capacity)	11.0kW
Frequency	50/60 Hz
Over Current Protection	None
Switch	None
Power Cable Wire Gauge	2.5mm <sup>2</sup> H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 3P + N + E, 16A, 230/400V, Splashproof IP44
Combined Total Receptacle/Socket Quantity	42
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	36
- Quantity per Phase	12
- Style	Banks of 6
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC C19
- Quantity on Face	6
- Quantity per Phase	2
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	66 in / 1683 mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes

## Specifications and Options (cont'd)

<b>Toolless Mounting Hardware — Center to Center Spacing</b>	1556 mm and 1645 mm
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55024
<b>Certification/Agency Approvals</b>	Complies with IEC 60950-1 (CB Certificate Available)
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	RCM Mark (EMC Only)
<b>Chassis Dimensions (HxWxD)</b>	1683mm x 51mm x 51mm

